09 / 508045 428 Rec'd PCT/PTO 03 MAR 2000

PCT WORLD INDUSTRIAL PROPERTY ORGANISATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED IN PURSUANCE OF THE PATENT CO-OPERATION TREATY (PCT)

(51) International Patent Classification ⁶:
A61B 17/39 A1

- (11) International Publication No:
- WO 99/11186 (43) International pr
 -) International publication date: 11th March 1999 (11.03.99)

- (21) International application No: PCT/DE98/02695
- (81) Designated States:

JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

- (22) International filing date: 4th September 1998 (04.09.98)
- Published

(30) Priority Data: 197 39 699.2 4th September 1997 (04.09.97) DE With international Search Report.

Prior to expiry of the period allowed for amendment in the claims; publication is repeated if amendments are received.

- (71) Applicants: (for all designated States except US):
 LASER- UND MEDIZIN-TECHNOLOGIE GGMBH, BERLIN [DE/DE];
 Krahmerstrasse 6-10, D12207
 Berlin (DE).
- (72) Inventors; and
- (75) Inventors/Applicants (only for US):
 MÜLER, Gerhard (DE/DE); And
 MÜLER, Gerhard (DE/DE); And
 Rehwiese 8, D-14129 Berlin (DE).
 DESINGER, Kai [DE/DE];
 Willmanndamm 10, D-10827 Berlin
 (DE). STEIN, Thomas [DE/DE];
 Kurfürstenstrasse 81, D-10787
 Berlin (DE).
- (74) Attorney: CHRISTIANSEN, Henning; Pacelliallee 43/45, D-14195 Berlin (DE)
- (54) Title: ELECTRODE ARRANGEMENT FOR ELECTROTHERMAL TREATMENT OF THE HUMAN OR ANIMAL BODY
- (57) Abstract

An electrode arrangement (82) for electrothermal treatment of the human or animal body, with at least one electrode arranged on an electrode carrier, for insertion into the body, which is connected to an alternating current source (81) by way of a supply line, and a temperature control device (84, 85) or influencing the effective temperature profile in the treatment region, wherein the electrodes carrier and the electrode or electrodes are designed for direct, in particular duct-forming insertion into body tissue, and the temperature control device has a time-controllable heating device (85) for thermal support of the insertion